

AXLES

Customer Name												
Beam Only				Axle Beam Round Diameter:								
				2K = 1-3/4"		3.5K = 2-3/8"						
				3.5K=3" Special Order								
				5.2 - 7K = 3"		8K = 3"						
				10K = 4"		12K/16K = 5"						
Spring Axle												
Customer Part Number												
Model #	2K	3.5K	4.4K	5.2K	6K	7K	8K	10K	12K	16K		
Axle Capacity												
Spindle Style												
				Straight		4" Drop		4" Drop up to 8K				
Lubrication Type (if grs)												
				Standard			Super Lube/Zerk					
Fluid Type												
				Oil		Grease						
Axle Type												
				Brake			Idler					
Brake Type												
			Electric	Disc	Hydraulic	Electric, Self Adjust			Air (12-16K)			
Brake Flange, Opt on 2K & 3.5K												
				Yes			No					
Tube Type												
				Standard			Heavy Wall					
Camber												
				Yes			No					
Bolt Pattern												
			Brake		475	545	550	555	655	865	8/275mm	
			Idler	440	475	545	550	555	655	865		
Stud Size												
			1/2"	5/8"	9/16"	M22						
Hub Face Dimension												
See Below												
Spring Center Dimension												
See Below												
Spring Orientation												
				Overslung			Underslung					
Spring Type												
				Double Eye			Slipper		No Springs			
Spring Length, Eye to Eye No Load												
			20"	23"	25"							

